



ALL MATERIAL TO BE 12 GA 304L S/S WITH A SANDBLASTED FINISH

ANTI-ENTRAPMENT COVER IS APPROVED FOR 675 GPM @ 1.5 F.P.S. DO NOT EXCEED

COVER HAS 144.3 SQ. IN. OF OPEN AREA

MAXIMUM SUMP SIZE 24" X 24"
 MINIMUM SUMP SIZE 18" X 18" (BASED ON 675 GPM)
 A SMALLER OR RECTANGULAR SUMP MAY BE POSSIBLE
 CONTACT YOUR DEALER FOR MORE INFORMATION

READ AND UNDERSTAND ALL INSTRUCTIONS AND WARNINGS BEFORE USE - OBTAIN COPY AT WWW.EUREKAMANUFACTURING.COM/WARNING.HTM VGB 2008

FOR SINGLE OR MULTIPLE DRAIN USE
 LIFE 20 YEARS COVER - 10 YEARS HARDWARE
 675 GPM - SUBMERGED SUCTION OUTLET
 CERTIFIED FOR WALL AND FLOOR USE
 EUREKA MANUFACTURING CO. AV32X32

ENLARGED VIEW OF ETCHING
 ETCHING LETTER HEIGHT IS .15"

DROP-IN ANCHORS (SHOWN) AND STUD ANCHORS PROVIDED

THE MANUFACTURER ASSUMES NO LIABILITY FOR INCORRECT INSTALLATION, AN INCORRECT SUMP, MISUSE OF THE PRODUCT, OR INCORRECT WATER CHEMISTRY

EUREKA MANUFACTURING CO.

PO BOX 1473 BISMARCK ND 58502

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND THE PROPERTY OF EUREKA MANUFACTURING CO. NO DUPLICATIONS WILL BE PERMITTED WITHOUT THE PERMISSION OF EUREKA MANUFACTURING CO.

Title 32" X 32" ANTI-ENTRAPMENT COVER

Scale NONE

Drawing No. AV32X32

Date 5-20-09

Drawn AKP

Chk.

Rev.